

1 Rugged Design: 3 Available Rockaway Sizes

ROCKAWAY LANDSCAPE RAKES PULL OUT 1/2" TO 8" ROCKS WITH EVERY PASS ON YOUR PROJECT. YOU CAN CUT DOWN INTO THE DIRT 3/4" WITH EACH PASS, ALLOWING YOU TO MAKE MULTIPLE PASSES AND GET ALL THE PROBLEM ROCKS OUT.



IDEALROCKAWAY.COM 717.723.6127

4415 ROCKAWAY - 44" WIDE

THE 4415 IS THE PERFECT ROCK RAKE FOR STAND-ON SKID STEERS. 10 GPM IS NEEDED As well as 1,000 LBS operating capacity. The 4415 is 44" wide and has a 70 Cubic Foot Collection Capacity.

7415 ROCKAWAY - 74" WIDE

THE 7415 IS 6FT WIDE AND FITS ON MOST WHEEL LOADERS AND SMALLER TRACK Loaders. 10 GPM is the minimum flow needed and 1,200 LBS operating capacity to use the 7415. It has 100 cubic feet of collection capacity and is 74" wide.

8415 ROCKAWAY - 84" WIDE

THE 8415 IS IDEAL'S LARGEST ROCKAWAY ROCK RAKE. IT IS 7FT WIDE AND BUILT FOR Bigger Track Loaders. 10 GPM is required as well as 1,350 LBS operating Capacity to run the 8415. It has a 120 cubic-foot collection capacity.

WHY CHOOSE A ROCKAWAY ROCK RAKE?

WHAT SETS OUR ROCK RAKES APART FROM THE COMPETITION? ROCKWAYS FEATURE A SIMPLE, RUGGED DESIGN THAT DOESN'T BREAK DOWN. You can trust that every time you hook up your rockaway it's going to pull out rocks and prep the soil. You'll get more work Done and save time on maintenance. Rockaways are durable, rugged, and reliable.

DURABLE. RUGGED. RELIABLE.

IDEAL ROCKAWAY

- REMOVES 1/2" TO 8" ROCKS
- SINGLE #80 CHAIN-DRIVE
- HARDOX STEEL ROTOR TEETH
- 13/8" ROTOR SHAFT & BEARINGS
- HYDRAULIC QUICK-ATTACH HOSES
- OPTIONAL SCREENING BUCKET UPGRADE
- METAL FRAME INCREASED 50%
- 3/16" STAINLESS STEEL WEAR RUNNERS
- 1/4" STEEL PUSH BAR ON FRONT OF HOOD
- STRONGER HOOD W/SOLID STEEL CENTER
- FRONT HOOD PORTING CONDITIONS SOIL
- CUSTOM ATTACHMENTS AVAILABLE



